Amendments to the Claims:

The listing of claims with replace all prior versions, and listings of claims in the

application:

Listing of Claims:

1. (previously amended): A method of manufacturing a floor panel, the method comprising

the steps of:

providing a panel body having a core, a top side of said core being provided with a top

surface layer, said panel body further having a side surface extending transversely to the top

surface layer;

forming a recess extending under the top surface layer from the side surface into the

panel body by leaving a freestanding ledge including said top surface layer, said recess having

opposing first and second recess surfaces; and

- closing said recess by fixing the first and second recess surfaces to one another, thereby

forming a floor panel having a beveled top edge with the top surface layer extending

continuously and in one piece from the top side of the core over the beveled top edge.

2. (previously amended): The method of claim 1 wherein said recess is wedge-shaped.

3. (previously amended): The method of claim 1 wherein said first recess surface is

arranged adjacent to and essentially parallel to said top surface layer.

4. (previously amended): The method of claim 1 wherein said first and second recess

surfaces are plain.

5. (previously amended): The method of claim 1, wherein the step of closing said recess

includes the step of applying adhesive.

6. (previously amended): The method of claim 1, wherein the step of closing said recess

includes the step of applying pressure to said ledge.

-2-

Appl. No. 10/525,282 Atty Docket No. BER-101-PCT/US

Amdt. dated May 12, 2008

7. (previously amended): The method of claim 1, wherein said ledge consists essentially of

said top surface layer.

8. (previously amended): The method of claim 1 wherein said floor panel includes a joining

element for connecting to a further joining element of an adjacent floor panel in a floor covering

formed by said floor panels, and the step of forming said recess includes the step of

simultaneously forming said joining element.

9. (previously amended): The method of claim 1 wherein the step of forming said recess

includes the step of removing material from said side surface adjacent to said recess to provide a

flushing side surface after having closed said recess.

10. (previously amended): A floor panel as manufactured by the method of claim 1.

11. (original): A method of manufacturing a floor panel, the method comprising the steps of:

providing a panel body having a core, a top side of said core being provided with a top

surface layer, said panel body further having a side surface extending transversely to the top

surface layer;

- forming a recess extending under the top surface layer from the side surface into the

panel body by leaving a freestanding ledge including said top surface layer, said recess having at

least two opposing recess surfaces; and

closing said recess by fixing the at least two opposing recess surfaces to one another.

thereby forming a floor panel having a beveled top edge with the top surface layer extending

continuously and in one piece from the top side of the core over the beveled top edge.

12. (original): The method of claim 11 wherein said recess is wedge-shaped.

13. (original): The method of claim 11 wherein one of the at least two opposing recess

surfaces is arranged adjacent to and essentially parallel to said top surface layer.

-3-

Appl. No. 10/525,282 Atty Docket No. BER-101-PCT/US

Amdt. dated May 12, 2008

14. (original): The method of claim 13 wherein the at least two opposing recess surfaces are

plain.

(original): The method of claim 11, wherein the step of closing said recess includes the 15.

step of applying adhesive.

16. (original): The method of claim 15, wherein the step of closing said recess includes the

step of applying pressure to said ledge.

17. (original): The method of claim 16, wherein said ledge consists essentially of said top

surface layer.

18. (original): The method of claim 16 wherein said floor panel includes a joining element

for connecting to a further joining element of an adjacent floor panel in a floor covering formed

by said floor panels, and the step of forming said recess includes the step of simultaneously

forming said joining element.

19. (original): The method of claim 18 wherein the step of forming said recess includes the

step of removing material from said side surface adjacent to said recess to provide a flushing side

surface after having closed said recess.

20. (original): A method of manufacturing a floor panel, the method comprising the steps of:

providing a panel body having a core, a top side of said core being provided with a top

surface layer, said panel body further having a side surface extending transversely to the top

surface layer;

forming a recess extending under the top surface layer from the side surface into the

panel body by leaving a freestanding ledge including said top surface layer, said recess having at

least two opposing recess surfaces;

closing said recess by fixing the at least two opposing recess surfaces to one another by

applying adhesives and applying pressure to said ledge, thereby forming a floor panel having a

-4-

Appl. No. 10/525,282 Atty Docket No. BER-101-PCT/US

Amdt, dated May 12, 2008

beveled top edge with the top surface layer extending continuously and in one piece from the top side of the core over the beveled top edge; and,

removing material from said side surface adjacent to said recess to provide a flushing side

surface after having closed said recess.

21. (original): The method of claim 20 wherein said recess is wedge-shaped.

22. (original): The method of claim 21 wherein one of the at least two opposing recess

surfaces is arranged adjacent to and essentially parallel to said top surface layer.

23. (original): The method of claim 22 wherein the at least two opposing recess surfaces are

plain.

24. (original): The method of claim 23, wherein said ledge consists essentially of said top

surface layer.

25. (original): The method of claim 24 wherein said floor panel includes a joining element

for connecting to a further joining element of an adjacent floor panel in a floor covering formed

by said floor panels, and the step of forming said recess includes the step of simultaneously

forming said joining element.

-5-

Appl. No. 10/525,282 Atty Docket No. BER-101-PCT/US Amdt. dated May 12, 2008